




280756



Adatto per linguetta sp. 1,20
(TO FIT 1,20mm TAB THK)

Sez. A-A

WIRE RANGE 3-6 mm²
(0.011-0.018 IN DIA. 2.4-4.1 mm)

1 OBSOLETE

PROIEZIONE AMERICANA

DIMENSIONS IN MM. DO NOT SCALE PRINT

L3	ECR-10-022530	KK	HMR	08FEB11	© 1976 BY TE INCORPORATED. ALL RIGHTS RESERVED. TE PRODUCTS COVERED BY PATENTS AND OR PATENTS PENDING.		CUSTOMER COPY REFERENCE ONLY	
L2	STARTEC UPDXTING		H.Y.		MATERIAL AND FINISH		TE Connectivity	
L1	REVISED ETOD-0225-99		H.G.	4-5 2000	1 4 OTTONE 2 OTTONE STAGNATO		CLASS	
B	DIM. 1,25±0,2 WAS 1,40			16/11/82	1 3 BRONZO FOSFOROSO 4 BRONZO FOSF. STAGNATO		TYPE	
A	IN PRODUZIONE			29- DIC.76	WIRE RANGE INSULATION 3÷6 mm ² 3,4÷5,1 mm		LOC NO	
1	P/N ERA 1A-76-5207			20/7/86	TOLERANCE EXCEPT AS NOTED ±0,3 · 1 · 0		REV	
LTR	REVISION RECORD	DR	CHK	DATE	SCALE 2:1		I A 280756	
DR	Joppe JULY 1976				NAME		L3	
CHK	APR 29/24/76				.375 SERIES FASTIN-FASTON RECEPTACLE			

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[280756-4](#)